

M O D E R N



W

S E R I E S

FACIAL · PALM VEIN · QR CODE · BLUETOOTH · SMART CARD · KEYPAD

Bluetooth and Contactless

W1



- Flush Mount Design
- Bluetooth and Contactless Dual Technology Reader
- Support 13.56 MHz, ISO 14443 A, & ISO 14443 B, ISO 15693, and Bluetooth 4.0
- Red / Green / Blue or mixed color LED square ring for visual notification
- User-defined reader's access granted/denied LED & buzzer ON/OFF time and interval
- Wiegand, OSDP standard, OSDP secure and the **ACX** proprietary scramble encryption format
- Bluetooth scan range: 1 to 10 meters
- Dimensions: 86mm (L) x 86mm (W) x 5mm (D)
- Waterproof IP65



Bluetooth



13.56 MHz



Waterproof IP65

QR Code


W2



- Flush Mount Design
- QR code, Bluetooth and Contact-less Multi Technology Reader
- Support 13.56 MHz, ISO 14443 A, & ISO 14443 B, ISO 15693, and Bluetooth 4.0 and QR code
- Red/Green/Blue or mixed color LED square ring for visual notification
- User-defined reader's access granted/denied LED & Buzzer ON/OFF time and interval
- Auto time synchronization when connected to internet
- Support fixed QR code and **ACX** scramble QR code format
- Wiegand, OSDP standard, OSDP secure, and the **ACX** proprietary scramble encryption format
- QR Code min. resolution: 5 mil, 1 mil = 0.0254 mm, invisible infra-red lights
- QR Code scanning angle: $\pm 60^\circ$ for left & right, $\pm 40^\circ$ for front and back, 360° rotation
- QR Code scan range: 4cm to 22 cm
- Bluetooth scan range: 1 to 10 meters
- Dimensions: 86mm (L) x 86mm (W) x 5mm (D)
- Waterproof IP65



Bluetooth



13.56 MHz



QR Code



Waterproof IP65

