


X8 Facial Recognition multi-technology reader supports Bluetooth, QR code and various kinds of Contactless Smart Card technologies. Its design is perfect for true-contactless and accurate cross-platform applications, from Smart Cards to mobile devices.

X8 Facial Recognition reader has live face detection, with less than 1 second for 5,000 users fast response time.

X8 reader is suitable for indoor installation. It is made of high-quality materials to enhanced reliability and longevity. The reader's output options include Wiegand and scramble encryption, catering to diverse security level requirements. The embedded Bluetooth technology as well as the QR code scanner also allow for reading encrypted virtual credential numbers from both Android and iPhone devices.



FEATURES

- Face liveness detection, less than 1 second (1:N) for 1000 users
- QR Code scanner with backlight, 4cm to 22cm read range
- Read the Scramble QR Code by ACX mobile apps for Access Control System
- Read the fixed QR code on mobile or label for Visitor Management System
- 2.4GHz Bluetooth 4.0+ works with ACX mobile apps
- 13.56Mhz Card technology includes LEGIC Prime and Advant, CSN for Mifare Classic, Mifare Plus, Mifare DESFire, SONY Felica, and PicoPass
- Red / Green / Blue or mixed LED color for visual notification, reader buzzer for audio notification
- User-defined reader's visual and audio notification for access granted and access denied
- Optical sensor for tamper protection, "I Am Alive" feature
- Reader outputs Wiegand and ACX proprietary scramble encryption RS485 format
- Reader LAN cable for clock synchronisation and Visitor Management System (API provided)
- Waterproof IP55

CARD TECHNOLOGY

Card Technology	Card Number Output	Item No. (RF / RF+BLE)
HID iCLASS	1 ~ 64 bits CSN ; HID card number	X811 / X8T1
HID 125 KHz	HID card number	X812 / X8T2
EM	1 ~ 40 bits CSN	X813 / X8T3
Mifare Classic 1K / 4K	1 ~ 56 bits CSN ; Custom data models	X814 / X8T4
SONY Felica CSN	1 ~ 64 bits CSN	X815 / X8T5
Mifare Plus S / X	1 ~ 56 bits ; Custom data models	X816 / X8T6
Mifare DESFire EV1 / EV2	1 ~ 56 bits ; Custom data models	X817 / X8T7
LEGIC Prime / Advant	1 ~ 64 bits ; Custom data models	X818 / X8T8

SPECIFICATIONS

X8 Facial Recognition Bluetooth QR Code Card Multi-Tech Reader	
Face Recognition Algorithm	Face+ +
Face Recognition Controller	Work with ACX 8800 Facial Recognition Controller or ACX 8808 Single Door Facial Recognition Controller
Face Detection	Live face detection speed time, 1:5000 in less than 1 second
Bluetooth	2.4 GHz Bluetooth 4.0
Reader Output	ACX Proprietary scramble RS485 output, max. 64 bits card number output
QR Code Min. Resolution	5 mil, 1 mil = 0.0254mm
QR Code Resolution	640 x 480
QR Code Scanning Angle	± 60° for left & right, ± 40° for front and back, 360° rotation
QR Code Scanning Range	4cm to 22cm
Typical Read Range	Bluetooth Technology : 0.5m to 10m, 13.56 MHz ISO card : 3cm to 8cm, 125 KHz ISO card : 6cm~10cm Typical read range achieved in air; different types of metal will cause some degradation Use spacers to space product off metal and improve read range if required
"I Am Alive"	User-defined 1 byte "I Am Alive" data at a certain interval
Reader Cable	Pigtall 10 wires
Mounting	Wall switch size, designed to mount and cover single-gang switch boxes primarily used in the Americas. It includes a slotted mounting plate for European and Asian back box spacing
Visual Indicator	LED line in Red / Green / Blue / Amber / Purple / White / Light Purple; user-defined LED ON / OFF time interval
Audio Indicator	Internal buzzer, user-defined beep sound ON / OFF time interval (ms)
Color	Black or White
Dimension	80mm x 130mm x 20mm
Product Weight	200g
Operating Voltage	9-16 VDC, Linear supply recommended
Operating Current	700mA AVG, 800mA PEAK
Operating Temperature	- 31° to 150° F (-35° to 65° C)
Storage Temperature	- 67° to 185° F (-55° to 85° C)
Operating Humidity	5% to 95% relative humidity non-condensing
Housing Material	Polycarbonate
Cable Distance	RS485 interface : 4000 feet (1200m), Wiegand interface : 500 feet (150m) Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent